

NAME

cluttex — a tool for processing TeX files

SYNOPSIS

cluttex -e *ENGINE* [options] [--] *FILE.tex*

DESCRIPTION

Process TeX files without cluttering your working directory.

The following options are accepted:

-e, --engine=ENGINE

Specify which TeX engine to use. *ENGINE* is one of the following: pdflatex, pdftex, lualatex, luatex, luajitex, xelatex, xetex, latex, etex, tex, platex, eptex, ptex, uplatex, euptex, uptex,

--engine-executable=COMMAND+OPTIONS

The actual TeX command to use. [default: *ENGINE*]

-o, --output=FILE

The name of output file. [default: *JOBNAME.pdf* or *JOBNAME.dvi*]

--fresh

Clean intermediate files before running TeX. Cannot be used with `--output-directory`.

--max-iterations=N

Maximum number of running TeX to resolve cross-references. [default: 3]

--start-with-draft

Start with draft mode.

--change-directory, --no-change-directory

Change directory before running TeX. [default: no]

--watch[=ENGINE]

Watch input files for change. Requires fswatch or inotifywait to be installed. *ENGINE* is one of 'fswatch', 'inotifywait' or 'auto'. [default: auto]

--tex-option=OPTION

Pass *OPTION* to TeX as a single option.

--tex-options=OPTIONS

Pass *OPTIONS* to TeX as multiple options.

--dvi-pdfmx-option=OPTION, --dvi-pdfmx-options=OPTIONS

Same for dvi/pdfmx.

--makeindex=COMMAND+OPTIONS

Command to generate index, such as 'makeindex' or 'mendex'.

--bibtex=*COMMAND+OPTIONS*
Command for BibTeX, such as ‘bibtex’ or ‘pbibtex’.

--biber[=*COMMAND+OPTIONS*]
Command for Biber.

--makeglossaries[=*COMMAND+OPTIONS*]
Command for makeglossaries.

-h, --help
Print this message and exit.

-v, --version
Print version information and exit.

-V, --verbose
Be more verbose.

--color[=*WHEN*]
Make ClutTeX’s message more colorful. *WHEN* is one of ‘always’, ‘auto’, or ‘never’. [default: ‘auto’ if Fl `-color` is omitted, ‘always’ if *WHEN* is omitted]

--includeonly=*NAMES*
Insert ‘\includeonly{*NAMES*}’.

--make-depends=*FILE*
Write dependencies as a Makefile rule.

--print-output-directory
Print the output directory and exit.

--package-support=*PKG1*[,*PKG2*,...]
Enable special support for some shell-escaping packages. Currently supported: minted, epstopdf.

--check-driver=*DRIVER*
Check that the correct driver file is loaded. *DRIVER* is one of ‘dvi_{pd}fm_x’, ‘dvips’, ‘dvisv_{gm}’.

--shell-escape, --no-shell-escape

--shell-restricted

--synctex=*NUMBER*

--fmt=*FMTNAME*

--file-line-error, --no-file-line-error
[default: yes]

--halt-on-error, --no-halt-on-error
[default: yes]

--interaction=*STRING*
[default: nonstopmode]

--jobname=*STRING*

--output-directory=*DIR*
[default: somewhere in the temporary directory]

--output-format=*FORMAT*
FORMAT is 'pdf' or 'dvi'. [default: pdf]

EXIT STATUS

The **cluttex** utility exits 0 on success, and >0 if an error occurs.