


## 02: How to compile

Boris Veytsman

TUG18 knitr workshop; July 2018\*

### 1 Using Rstudio



---

\*This work is licensed under a Creative Commons Attribution 4.0 International License (CC-BY)

## 2 Using Makefiles

```
# This work is licensed under a Creative Commons Attribution 4.0  
# International License (CC-BY)
```

```
RNW = \  
    01_intro.rnw \  
    02_compilation.rnw \  
    03_setup.rnw \  
    04_tidy.rnw \  
    05_machine_learning.rnw \  
    06_tikz.rnw
```

```
TEXDERIVED = ${RNW:%.rnw=%.tex}
```

```
TEX = $(TEXDERIVED)
```

```
PDF = ${TEX:%.tex=%.pdf}
```

```
all: ${PDF}
```

```
%.pdf: %.tex  
    pdflatex $*  
    - bibtex $*  
    pdflatex $*  
    - while (grep -q '^LaTeX Warning: Label(s) may have changed' $*.log) \  
    do pdflatex $*; done
```

```
%.tex: %.rnw  
    Rscript -e "library('knitr'); _knit('$<')"
```

```
clean:
```

```
$(RM) *.aux *.bbl *.dvi *.log *.out *.toc *.blg *.lof *.lot \  
*.eps *.ps *.lol *.tex *.synctex.gz *.zip *-tikzDictionary  
$(RM) -r figure ??_figures *
```

```
distclean: clean
    rm -f ${PDF}

zip: all clean
    cd ..; \
    zip -r knitr-workshop.zip workshop \
    -x '*' -x '*.tgz' -x '*.zip' -x '*/CVS' -x '*/CVS/*'; \
    mv knitr-workshop.zip workshop
```